

## BITUMEN PRIMER Nr.01 / BITUMEN PRIME COATING

Bitumen Primer / Bitumen Primer (Concentrate)

### Description of material

The primer presents a mix of high-quality bituminous solution which is formulated using specially selected organic solvents. It has an enhanced dampening ability, high penetration and short drying time. Ready for use primer is applied to the base at once, which offers additional convenience and enhanced performance.

### Application areas

The primer is used to prepare (prime) substrates prior to the application of bituminous torch-applied or self-adhesive waterproofing membranes. In particular, the prime coating helps to ensure the strong adhesion of the waterproofing membranes to porous, rough and dusty surfaces.



### Method of application

Ready to use primer is applied to a surface by roller, large or small brush. It is applied to the base at once that grants additional convenience and enhanced performance.

### Consumption

0.25–0.35 l/m<sup>2</sup> (1 l of primer per 3.33 m<sup>2</sup>).

### Packing

Bucket 10 and 20 liters.

### Storage

The product should be stored in a dry place protected from direct sunlight at temperatures from -20°C to +30°C. Shelf life – 18 months.

Property	Value
Drying time at 20°C, h	12
Mass fraction of non-volatile substances, %	45 - 55
Softening temperature, °C	≥ 70
Relative viscosity, s	15 - 40

### Technical Service and Other Products

Specialist advice and information on other compatible products can be found at [www.wonderbuilds.co.uk](http://www.wonderbuilds.co.uk)