

BITUMEN PRIMER Nr.03

Fast drying bitumen primer coating

Description of material

BITUMEN PRIMER Nr.03 is a high-quality, fast-drying bituminous solution which is formulated using a special blend of bitumen, polymers and adhesion additives in selected organic solvents. BITUMEN PRIMER Nr.03 is a ready-to-use primer that offers high penetration, fast-track application and reliable performance.

Application areas

The primer is used to seal and prepare (prime) substrates prior to the application of bituminous torch-applied or self-adhesive waterproofing membranes. In particular, the prime coating helps to ensure the strong adhesion of the waterproofing membranes to porous, rough and dusty surfaces.



Method of application

Ready to use primer can be applied to the prepared surface using large or small paint brushes. As the primer is brushed into the surface, it saturates and attaches itself to the substrate, ensuring a strong adhesion of the subsequent waterproofing membrane.

BITUMEN PRIMER Nr. 03 can be applied in temperatures between -20°C and +40°C.

In temperatures below +5°C, the product should be stored in a warm room for at least 24 hours prior to application. Do not use near naked flames and always apply in well ventilated areas. Avoid contact with skin and eyes.

Consumption

0.25–0.30 l/m² (1 l of primer per 3.33 m²).

Packing

Bucket 20 liters.

Storage

The product should be stored in a dry place protected from direct sunlight at temperatures from -20°C to +30°C. Shelf life – 18 months.

Property	Value
Drying time at 20°C, minutes	10
Relative viscosity, s	10 - 30
Dry residue, %	Approx. 25 - 30

Technical Service and Other Products

Specialist advice and information on other compatible products can be found at www.wonderbuilds.co.uk