

WONDERBUILDS 5.5KG T-20C SBS MINERAL

Torch-Applied, SBS Modified Bituminous Cap Sheet

Introduction & Product Description

WONDERBUILDS 5.5KG T -20C SBS BLACK MINERAL is a high-performance polyester based waterproofing material designed to suit requirements of both new build and remedial roofing applications. It is a reliable, environmentally friendly membrane with excellent performance and economy characteristics.

Product Features

- High quality polyester carrier
- Excellent low temperature flexibility at -20°C
- High puncture resistance and high resistance to foot marking
- SBS modified bitumen binder formulated to ensure high performance and life expectancy

Availability

Product Name	Colour	Product Code	Roll Dimensions (m)	Weight(kg/m²)
WonderBuilds 5.5KG T	Black	WB55TBME	1 X 8	5.5
-20C SBS Black Mineral				

Performance

Essential Characteristics	Test Method	WonderBuilds 5.5KG T
		-20C SBS Black Mineral
Length, m	EN 1848-1	8 ± 3cm
Width, m	EN 1848-1	1 ± 2cm
Straightness	EN 1848-1	PASS
Weight of square meter, kg	EN 1849-1	5.5 ± 0.1



Essential Characteristics	Test Method	WonderBuilds 5.5KG T
		-20C SBS Black Mineral
Visible Defects	EN 1850-1	PASS
Water tightness	EN 1928 method A	PASS
Reaction to fire	EN 13501-1	E
External fire performance	EN 13501-5	NPD
Resistance to tearing, N	EN 12310-1	150 ± 20%
Tensile strength, N/50mm	EN 12311-1	800 L / 600 T ± 20%
Elongation at maximum load	EN 12311-1	35 ± 20%

Storage

Store rolls on end on a firm, clean base in a cool, dry place and protect from direct sunlight.

Technical Service and Other Products

Specialist advice and information on other compatible products can be found at www.wonderbuilds.co.uk.