



1E TOP TRADE GREEN FELT 1 X 10M

Waterproofing membrane

Description

1E Top Trade Green Felt is a single layer bitumen felt for the roofs of non-habitable structures. This product can be used as an economical underlay or capsheet within a built-up felt roofing system. It can also be used as an underlay to bitumen shingles in a boarded pitched roof application. 1E Top Trade Green Felt consists of a reinforced glass fibre base that is coated with a modified bitumen and finished with a Slate Mineral on the topside and fine sand to the underside.

Performance and Composition

Composition: Modified Bitumen

Finish: Mineral

Length: 10m

Width: 1m

Roll Weight: 3kg per sqm

Carrier: Reinforced Glass Fibre

Product Code: WB1E02

Methods Of Application

MATERIAL HANDLING

Checking: Material should be checked to ensure that they conform to the project specification.

Handling: Material should be unloaded and handles with care to avoid damages.

Site Storage: Material should be stored on end on a firm, level clean base protected from direct sunlight.

PRIOR TO COMMENCEMENT

Application must always follow good, safe working practice. Prior to commencing works it is advisable that the work area irrespective of levels of competence, ensuring all works are being planned and undertaken in a safe, pragmatic manner. Temperature should be considered, as works undertaken ideally at temperatures over 10°C. Avoid installing in wet or very cold weather.

PREPARATION

Before starting on the roofing works, the installer should ensure the surfaces receiving the felt are sound, clean and dry. All existing old roof felt should be removed, and the roof structure should be checked for adequacy and strength prior to new work being done.

Further Information

View our full range of products at www.wonderbuilds.co.uk.

You can also contact us at 0208 208 2121, or at admin@wonderbuilds.co.uk.